jaquar.com	JOQUOL BATH+LIGHT
Document No.	
SNW/CNS/24/959NUF	
545	
	230 25X56mm
-510 ( ( ) <del>165</del>	
Ø16	
	F.F.Lvl. Ø100
	SIDE VIEW
TOP VIEW	SIDE VIEW BACK VIEW
General Information	
Product Code	CNS-WHT-959NUF
Brand	Jaquar
Colour	White
Туре	Wall Hung WC
Material	Ceramic-Vitreous China (VC)
Product Specification	
Product Dimension	380X545X375 mm
Bowl Opening (Inner Dimension)	270x335 mm
Product Net Weight	21 kg
Product Gross Weight	25 kg
Packaging Dimension	450x380x560mm
Outlet	Horizontal
Outlet Hole Dimension	External diameter of outlet hole dia. Ø 100 ± 5 mm
	Vertical distance between the Floor and the centre line of the waste outlet hole ≤ 220 mm
	Rimless ,Regular, Dual & I Flush advantages.
Product Features	UF Soft Close Seat Cover,Complere Trap Glaze, Dual Flushing-3/6 LPF,Anti germ glaze.
ACCESSORIES PROVIDED	
Seat Cover	CNS-WHT-115UF
Inlet & Outlet gasket	ZPS-WHT-GK01
ACCESSORIES RECOMMENDATION	1
Rag bolt	ZPS-MST-RB07
Concealed cistern	JCS-WHT-2400S, 2400P, 2400, 2400WS, 2400WP, 2400FS, 2400FP, 2431P, 2431FP, 2431, 2431S, 2431FS
CARE AND CLEANING GUIDELINES	
- Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and	
use thereafter.	
$\neg$ The product is heavy and it is recommended the	at two persons hold it while it is being fixed.
- Carefully inspect the new product for damage before installation.	
-, Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.	
¬ Risk of external leakage. Do not lift or rock the bowl after placement.	
- Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.	
- Do not allow cleaners to sit or soak on the product.	
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.	
- Wipe surfaces clean and rinse completely with water immediately after applying cleaners.	
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.	
¬ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.	
QUALITY MANAGEMENT SYSTEM - ISO 9001	
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product	
Prepared by Marech Lem	Checked by Approved by