

jaquar.com Document No. SNW/OPS/24/801PM








TOP VIEW





General Information	
OPS-WHT-15801PM	
Jaquar	
White	
Wall Hung Basin	
Ceramic-Vitreous China (VC)	
Product Specification	
600x440x155 mm	
520x300x110 mm	
15.5 kg.	
16.5 kg.	
610x450x170 mm	
Vertical	
Tap hole dia. Ø 35 ± 2 mm	
Outlet Hole Dimension Internal diameter of outlet hole dia. Ø45 +2/-1 mm	
Horizontal distance between the center line of the tap hole and the center line of the waste outlet hole ≤ 145 mm	
Integrated Design With Tap Hole , anti germ glaze	
ACCESSORIES INCLUDED	

CARE AND CLEANING GUIDELINES

Rag bolt

- Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- The product is heavy and it is recommended that two persons hold it while it is being fixed.

ZPS-MST-RB03

- ¬ Carefully inspect the new product for damage before installation.
- ¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- \neg Risk of external leakage. Do not lift or rock the bowl after placement
- ¬ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ¬ Do not allow cleaners to sit or soak on the product.
- ¬ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ¬ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

QUALITY MANAGEMENT SYSTEM - ISO 9001



DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.
For Installation Refer Actual Product