

General Information	
General Information	
CNS-WHT-759S300UFSMZ	
Jaquar	
White	
Coupled WC (S trap 300)	
Ceramic-Vitreous China (VC)	
Product Specification	
350x660x790 mm	
260X345 mm	
41.0 Kg	
44.0 Kg	
850X440X460mm	
Vertical	
Horizontal distance between the wall and the centre line of the waste outlet hole ≤ 300 mm	
Stylish Rimless Design With Curvey Shape UF Slim Soft Close Seat Cover Dual Flush 3 and 6 LPF Anti Bacterial Glaze on Ceramic Anti Bacterial Seat Cover Smooth Glaze Surface Material - Vitreous China (VC)	
ACCESSORIES INCLUDED	
CNS-WHT-123UF	
ZPS-SNS-FB02	
CNS-WHT-217C	
ZCF-WHT-FT003	
ZPS-WHT-1401	

CARE AND CLEANING GUIDELINES

- ¬ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- \neg Carefully inspect the new product for damage before installation.
- \neg Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ¬ Risk of external leakage. Do not lift or rock the bowl after placement.
- Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ¬ Do not allow cleaners to sit or soak on the product.
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- n Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- ¬ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

QUALITY MANAGEMENT SYSTEM - ISO 9001



DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.
For Installation Refer Actual Product